

BESTOLIFE STORAGE COMPOUND



5 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color: **Off-White**

Weight/Gallon: **8.1 pounds/gallon**

Dropping Point: **350°F/177°C (typ)**

Flash Point: **385°F/196°C (min)**

Brushable To: **10°F/-12°C**

ASTBM B117 Salt Spray Test: **4000 hrs (min)**

Contains: **Corrosion and oxidation inhibitors and polymers**

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
640235	5 gallon	35 pounds metal

DESCRIPTION

BESTOLIFE Storage Compound (BSC) provides long-term storage protection for threaded surfaces in a variety of conditions. Laboratory tests confirm superior storage protection equaling 4000 hours.

APPLICATIONS

For long-term storage.

TECHNICAL DATA

BSC is a long-term storage compound designed to protect all types of threaded surfaces from rust and corrosion caused by exposure to different types of atmospheric and environmental storage conditions. Salt spray tests comparing this compound with other commercially available storage compounds have proved the superior corrosion resistance of BSC.

BSC applies easily in all working conditions and will not run off or "bleed" at high temperatures. To assure a good seal and protect against galling threads, all storage compounds should be cleaned off before a thread compound is applied. Thread compounds can become liquid and run off connections causing sealing and galling problems, when they are incompatible with storage compounds.

NOTES

A material safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.



BESTOLIFE
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

BESTOLIFE.COM