

# BESTOLIFE ZN-18



5 Gallon Plastic Pail

## PRODUCT CHARACTERISTICS

Color: <b>Gray</b>
Penetration: <b>300-320 (ASTM D 217)</b>
Weight/Gallon: <b>12.5 pounds/gallon</b>
Dropping Point: <b>350°F/177°C (typ)</b>
Flash Point: <b>385°F/196°C (min)</b>
Brushable To: <b>10°F/-12°C</b>
Friction Factor: <b>0.90 (relative API Modified)*</b>
Contains: <b>Zinc and other nonmetallic additives</b>

## PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
620015	2 gallon	15 pounds plastic
620060	5 gallon	60 pounds plastic

## DESCRIPTION

BESTOLIFE ZN-18 is a zinc-based thread compound designed to resist corrosion, pitting, and discoloration on threaded connections subjected to long-term storage.

## APPLICATIONS

Zinc-based compound for light duty drilling and pipe storage.

## TECHNICAL DATA

ZN-18 will also provide galling and seizing protection for threaded connections used in light duty applications. Contains 18% powdered metallic zinc, as well as H<sub>2</sub>S, rust and corrosion inhibitors.

## NOTES

A material safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

---

\*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.



**BESTOLIFE**  
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

**BESTOLIFE.COM**